

SAFETY DATA SHEET

ACDELCO TRANSFER CASE FLUID

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

ACDELCO TRANSFER CASE FLUID

Product no.

88861950

Unique formula identifier (UFI)

WWJ5-Q022-600H-UVQM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricating Oil

Uses advised against

The product may only be used in accordance with the area of application specified above. If, nonetheless, the product is used outside the specified scope, please contact the supplier.

1.3. Details of the supplier of the safety data sheet

Company and address

Klintberg & Way Parts AB

Haukadalsgatan 5

164 40 KISTA

Sweden

+46 (0)8 6808800

www.kwparts.com

E-mail

info@kwparts.com

Revision

09-03-2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Sens. 1; H317, May cause an allergic skin reaction.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

May cause an allergic skin reaction. (H317)
 Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
 Keep out of reach of children. (P102)

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
 Do NOT induce vomiting. (P331)

Storage

-

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
 Benzene, polypropene derivs., sulfonated, calcium salts
 Distillates (petroleum), hydrotreated middle

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]	CAS No.: 64742-53-6 EC No.: 265-156-6 REACH: Index No.: 649-466-00-2	5-<10%	Asp. Tox. 1, H304	
Benzene, polypropene derivs., sulfonated,	CAS No.: 75975-85-8	1-<5%	Skin Sens. 1, H317 Eye Irrit. 2, H319	

calcium salts	EC No.: 616-278-7		
	REACH:		
	Index No.:		
Distillates (petroleum), hydrotreated middle	CAS No.: 64742-46-7	1-<5%	Asp. Tox. 1, H304 Skin Irrit. 2, H315 Acute Tox. 4, H332 Aquatic Chronic 2, H411
	EC No.: 265-148-2		
	REACH: 01-2119489867-12-XXXX		
	Index No.: 649-221-00-X		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	CAS No.: 68649-42-3	1-<2.5%	Skin Irrit. 2, H315 Eye Irrit. 2, H319
	EC No.: 272-028-3		
	REACH: 01-2120742271-64-XXXX		
	Index No.:		

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

No special

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of uncertainty on how to treat an exposed person, call the National Poisons Information Service immediately.

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

To avoid irritation flush with soft water jet or eye wash fluid for at least 5 minutes. In case of persistent symptoms (intense burning, pain, sensitivity to light, visual disturbance) continue flushing and contact/seek a hospital or doctor.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER / doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical

pneumonia may appear after several hours.

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Always wear gloves and protective clothing when in contact with chemical substances.

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A risk assessment of the handling shall always be prepared based on the specific conditions prevailing at the workplace. The risk assessment shall be used as basis for preparing appropriate instructions for the safe handling of the product.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	740 µg/kgbw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	1.19 mg/m³
Route of exposure	Inhalation
Duration	Long term – Local effects - General population

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	970 µg/kgbw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	5.58 mg/m³
Route of exposure	Inhalation
Duration	Long term – Local effects - Workers

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100
-------------------	---

°F (19cSt at 40 °C). It contains relatively few normal paraffins.]
 DNEL 2.73 mg/m³
 Route of exposure Inhalation
 Duration Long term – Systemic effects - Workers

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 16.4 mg/m³
 Route of exposure Inhalation
 Duration Long term – Systemic effects - Workers

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 2.91 mg/kg bw/day
 Route of exposure Dermal
 Duration Long term – Systemic effects - Workers

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 1.25 mg/kg bw/day
 Route of exposure Oral
 Duration Long term – Systemic effects - General population

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 1.25 mg/kg bw/day
 Route of exposure Dermal
 Duration Long term – Systemic effects - General population

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 3001.6 mg/m³
 Route of exposure Inhalation
 Duration Short term – Systemic effects - General population

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 4.85 mg/m³
 Route of exposure Inhalation
 Duration Long term – Systemic effects - General population

Product/substance Distillates (petroleum), hydrotreated middle
 DNEL 5002.67 mg/m³
 Route of exposure Inhalation
 Duration Short term – Systemic effects - Workers

PNEC

Product/substance Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
 PNEC 9.33 mg/kg
 Route of exposure Predators
 Duration of Exposure

Product/substance Distillates (petroleum), hydrotreated middle
 PNEC 17000 mg/kg food

Route of exposure	Predators
Duration of Exposure	Continuous

8.2. Exposure controls

Control is unnecessary if the product is used as intended.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

In case of simultaneous exposure to several air pollutants, their combined effects shall be considered. In assessing exposure conditions, the body weight and absorption of certain substances through the skin shall be taken into account in addition to the concentration of air pollutants in inhaled air. The person who plans and carries out the air pollution measurement shall have sufficient knowledge to do so. Measurements shall be taken using appropriate methods and equipment. Exposure measurements relate to conditions during normal operation. Where necessary, they shall also highlight the exposure under other conditions. Exposure measurements shall be taken in the breathing zone on a sufficient number of persons to make it possible to assess the exposure of all exposed persons.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment


Generally

Use only CE marked protective equipment.


Respiratory Equipment

Type	Class	Colour	Standards	
Respiratory protection is not needed in the event of adequate ventilation.				
Combination filter A + P3	If there is a risk of exposure to vapor or aerosol, use combination filter against organic gases and vapors (type A), and particulate filter (type P3).	Brown/White	P3 (EN 140, EN 143, EN 149)	

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	> 0,4	> 480	EN374	

Eye protection

Type	Standards
No specific requirements	-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Amber

Odour / Odour threshold

Characteristic

pH

No data available

Density (g/cm³)

No data available

Relative density

0.875 (15 °C)

Kinematic viscosity

34 centistokes (40 °C)

Particle characteristics

No data available

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

316

Vapour pressure

< 0.013 kPa (20 °C)

Relative vapour density

> 2

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

> 192

Ignition (°C)

No data available

Auto flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

> 3.5

Solubility in fat (g/L)

No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

No special

Endocrine disrupting properties

No special

Other information

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

15 01 10* Packaging containing residues of or contaminated by dangerous substances

Specific labelling

Before handling waste, see Section 8, Exposure controls/personal protection. Contamination of the product with hazardous substances during use cannot be ruled out and therefore the properties of the waste do not fully correspond to those of the original product. It is therefore always the user's responsibility to classify the waste.

Hazardous waste shall be transported to an approved waste facility by an authorised carrier.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1. - 14.4.

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

MARINE POLLUTANT

No

IATA

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Tactile warning.

Sources

The employer is obliged to continuously keep abreast of the current regulations pertaining to the activity in question.

The Management of Health and Safety at Work Regulations 1999

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Future Competence Sweden AB

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en