

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

C H R Y S L E R

HAZARD COMMUNICATION SHEET

303973 DRAFT PART/COMMTY CD: 68218920GA
PREPARATION DATE: 08-09-13 STNDRD: N/AV SUPPLIER: 90117 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE FCA US LLC
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE FCA US LLC
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
FCA US LLC INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR MAXPRO SAE 5W-30 ENGINE OIL GF-5
MFG ID : N/AV
DESCRIPTION: OIL 5W30

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
PARAFFINIC PROCESS OIL 60-100 W 5 5 5 MG/M3
064742-54-7A DISTILLATES (PETROLE L N/AP 10 10
4,7-METHANO-1H-INDENE, 3A,4,7,7A- 1-5 W N/AV N/AV N/AV N/AV
025034-71-3 4,7-METHANO-1H-INDEN
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: PETROLEUM OIL, POLYMER(S) AND
ADDITIVES.

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : > 536 F SOLUB IN WATER: NEGLIGIBLE (< 0.1%)
VAPOR PRESSURE: N/AV EVAP. RATE: N/AV REF: N/AV
VAPOR DENSITY : > 1.000 AT N/AV SPECIFIC GRAVITY: N/AV
PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AP
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: 1000000.00
APPEARANCE & ODOR: COLOR: AMBER..... STATE: LIQUID.....-ODOR: SLIGHT.....,
ODOR: HYDROCARBON.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: 428 F COC IGN TEMP: 608 F LEL: 1.000% UEL: 10.000%
SPECIAL FIRE & EXPLOSION HAZARDS:

**Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB**

MATERIAL WILL BURN IN A FIRE.

EXTINGUISHING MEDIA:

FOAM OR WATER FOG. SMALL FIRE-DRY CHEMICAL, CARBON DIOXIDE OR SAND.

SPECIAL FIREFIGHTING PROCEDURES:

DO NOT USE WATER IN STRAIGHT STREAMS. USE PROTECTIVE CLOTHING. USE
SELF-CONTAINED BREATHING APPARATUS FOR ENCLOSED AREAS.

SENSITIVE TO MECHANICAL IMPACT?: N/AP SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE AND TRACES OF INCOMPLETELY BURNED
CARBON COMPOUNDS.

FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INHALATION--->> SHOULD NOT BE HARMFUL. MIST-HIGH CONCENTRATION MAY
PRODUCE THE FOLLOWING: IRRITATION. <<---SKIN CONTACT--->> CHRONIC EXPOSURE
MAY PRODUCE THE FOLLOWING: OIL ACNE AND FOLLICULITIS. <<---EYE CONTACT--->>
DIRECT CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION AND TEARING.
<<---INGESTION--->> SHOULD NOT BE HARMFUL. <<---MEDICAL CONDITIONS WHICH MAY
BE AGGRAVATED BY THIS PRODUCT--->> SKIN DISORDERS. <<---SPECIAL
TOXICITY--->> USED MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER IN
LABORATORY ANIMALS.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> SHOULD NOT BE HARMFUL. REMOVE TO FRESH AIR AT ONCE. IF
CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE
CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS,
CONSULT A PHYSICIAN. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE
AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE
FOR 15 MINUTES. IF CONDITION PERSISTS, CONSULT A PHYSICIAN.
<<---INGESTION--->> SHOULD NOT BE HARMFUL. LARGE QUANTITIES-CONTACT A
PHYSICIAN.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE, FREEZING (DO NOT FREEZE). SUNLIGHT.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

UNKNOWN..

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WEAR PROTECTIVE CLOTHING. SPILLS ARE VERY SLIPPERY. USE OIL ABSORPTION COMPOUND CONTAIN WITH EARTH OR SAND TO PREVENT ENTERING DRAINS. PREVENT GROUNDWATER CONTAMINATION. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS.

WASTE DISPOSAL METHODS:

DO NOT FLUSH INTO SEWER SYSTEM. DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL DISPOSAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. THE FOLLOWING MAY BE NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED: MIST RESPIRATOR OR ORGANIC VAPOR RESPIRATOR AND. USE A MIST PREFILTER..

VENTILATION TYPE:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. THE FOLLOWING MAY BE NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED: LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

NEOPRENE GLOVES, POLYVINYLCHLORIDE (PVC) GLOVES OR NITRILE RUBBER GLOVES.

EYE PROTECTION:

SAFETY GLASSES OR CHEMICAL FULL FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE AT TEMPERATURE BELOW 120 F (49 C). DO NOT FREEZE. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID BREATHING MIST. WASH THOROUGHLY AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. AVOID SPONTANEOUS COMBUSTION OF CONTAMINATED RAGS OR OTHER EASILY IGNITABLE MATERIAL BY IMMEDIATE IMMERSION IN WATER.

OTHER PRECAUTIONARY MEASURES:

REACTS WITH OXIDIZERS.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

INFORMATION UNAVAILABLE AT THIS TIME