

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

C H R Y S L E R
HAZARD COMMUNICATION SHEET

193842
PREPARATION DATE: 05-23-11 STNDRD: N/AV
OSHA HAZ: YES HAZWOPER HAZ: YES

PART/COMMTY CD: 05103523EA
SUPPLIER: 47123 MFGR: 03500
CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE FCA US LLC
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE FCA US LLC
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
FCA US LLC INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: 3-7057LV AUTOMOTIVE SEALANT
MFG ID : 3-7057LV
DESCRIPTION: SEALANT-RTV

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
SILICA, AMORPHOUS (FUMED) 10-30 W 6 10 6 MG/M3
007631-86-9 SILICA (8CI9CI)
CARBON BLACK 1-5 W 3.500 3 3.500 MG/M3 I2B
001333-86-4 CARBON BLACK
METHYLTRIACTOXYLSILANE 1-5 W N/AP N/AP N/AP N/AP
004253-34-3 SILANETRIOL, METHYL-
SILANETRIOL, ETHYL-, TRIACETATE (1-5 W N/AV N/AV N/AV N/AV
017689-77-9 SILANETRIOL, ETHYL-,
POLY(DIMETHYLSILOXANE) 1-5 W N/AP N/AP N/AP N/AP
063148-62-9 SILOXANES AND SILICO
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: SILICA CONTAINING COMPOUNDS AND
PIGMENT(S).

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : N/AV SOLUB IN WATER: N/AV
VAPOR PRESSURE: N/AV EVAP. RATE: N/AV REF: N/AV
VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 1.070 AT 77 F
PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: COLOR: BLACK..... STATE: PASTE..... ODOR: ACETIC ACID

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

(VINEGAR).....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: N/AV COC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS. MAY REACT WITH OXIDIZERS AND WITH WATER.

EXTINGUISHING MEDIA:

SMALL FIRE-DRY CHEMICAL, FOAM OR WATER. SMALL FIRE-CARBON DIOXIDE, DRY CHEMICAL OR WATER. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SPECIAL FIREFIGHTING PROCEDURES:

AVOID BREATHING VAPOR OR FUMES. USE SELF-CONTAINED BREATHING APPARATUS. USE PROTECTIVE CLOTHING. IF CERTAIN THAT CONTAINERS REMAIN SEALED, WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. REMOVE CONTAINERS FROM FIRE AREA IF POSSIBLE.

SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO

HAZARDOUS COMBUSTION PRODUCTS:

SILICON DIOXIDE, FORMALDEHYDE, TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS, CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AV

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INHALATION--->> VAPOR MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. MAY BE IRRITATING TO EYES, NOSE, AND THROAT. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: MINOR IRRITATION.. SKIN CONTACT MAY PRODUCE DEFATTING AND DRYING OF SKIN. <<---EYE CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION AND TEARING. <<---INGESTION--->> MAY BE HARMFUL IF SWALLOWED. MAY CAUSE UPSET STOMACH, NAUSEA, VOMITING AND DIARRHEA.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF PULMONARY SYMPTOMS DEVELOP, CONSULT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---EYE CONTACT--->> REMOVE CONTACT LENSES TO ASSURE COMPLETE FLUSHING. RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

HIGH TEMPERATURE AND EXPOSURE TO HUMIDITY.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS AND WATER.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION MAY PRODUCE THE FOLLOWING: SILICON DIOXIDE,
FORMALDEHYDE, TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS, CARBON
MONOXIDE AND CARBON DIOXIDE.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WEAR PROTECTIVE CLOTHING. WEAR RESPIRATORY PROTECTION. AVOID BREATHING
VAPORS. VENTILATE AREA. SMALL SPILL-WIPE UP OR SCRAPE UP SMALL SPILL OR
RESIDUE. LARGE SPILL-PROVIDE ADEQUATE VENTILATION. CONTAIN WITH EARTH OR
SAND TO PREVENT ENTERING DRAINS. SHOVEL INTO STORAGE CONTAINERS. DISCARD
INTO SEALED CONTAINERS FOR DISPOSAL. RESIDUE CAN BE REMOVED WITH A
NON-FLAMMABLE SOLVENT.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND
FEDERAL DISPOSAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. THE FOLLOWING MAY BE
NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED: ORGANIC VAPOR RESPIRATOR
OR AIR-SUPPLIED RESPIRATOR.

VENTILATION TYPE:

THE FOLLOWING IS USUALLY ADEQUATE: GOOD GENERAL VENTILATION. TO MAINTAIN
THE TLV, THE FOLLOWING MAY BE NEEDED: LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE EQUIPMENT:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. A SAFETY SHOWER MAY
BE NEEDED FOR EMERGENCY SITUATIONS. AN EYE WASH MAY BE NEEDED FOR EMERGENCY
SITUATIONS.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A DRY PLACE-AVOID MOISTURE DURING STORAGE. STORE IN A WELL
VENTILATED AREA. USE WITH ADEQUATE VENTILATION. KEEP FROM HEAT, SPARK OR

Global Parts Order Processing
Material Safety Data Sheet
KLINTBERG & WAY AB

OPEN FLAMES. STORE AWAY FROM DIRECT SUNLIGHT. STORE SEPARATE FROM INCOMPATIBLE MATERIALS. REACTS WITH OXIDIZERS. REACTS WITH WATER. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID).

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID EYE CONTACT. AVOID INGESTION. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY AFTER USING. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP

NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

INFORMATION UNAVAILABLE AT THIS TIME